

RECEIVED  
CENTRAL FAX CENTER  
APR 22 2008

DOCKET NO. 2003.10.010.NS0  
U.S. SERIAL NO. 10/810,302  
PATENT

IN THE CLAIMS

The current claims follow. For claims not marked as amended in this response, any difference in the claims below and the previous state of the claims is unintentional and in the nature of a typographical error.

1. (Currently Amended) For use in a telecommunication network, an apparatus for testing a telecommunication device comprising switching fabric including a plurality of voice paths, said apparatus comprising:

a test controller configured to receive a test call initiation message directed to the test controller from an originating terminal, to prompt the telecommunication device to allocate one of the voice paths within the telecommunication device for [[the]] a test call based on the test call initiation message, and to establish a call connection for the test call between the originating terminal and a destination terminal via the allocated voice path and a packet-switched network to test the allocated voice path.

2. (Original) The apparatus as set forth in Claim 1 wherein the voice paths comprise time division multiplexed (TDM) switched circuits.

3. (Original) The apparatus as set forth in Claim 1 wherein the originating terminal and the destination terminal are Session Initiation Protocol (SIP) phones.

LASAMS01\00320

-2-

DOCKET NO. 2003.10.010.NS0  
U.S. SERIAL NO. 10/810,302  
PATENT

4. (Currently Amended) The apparatus as set forth in Claim 3 ~~wherein said test controller is configured to receive a signaling message for the test call from the originating terminal, the signaling the test call initiation~~ message being addressed to an Internet Protocol (IP) address of said test controller.

5. (Currently Amended) The apparatus as set forth in Claim 4 wherein the signaling test call initiation message is an INVITE message.

6. (Original) The apparatus as set forth in Claim 4 wherein said test controller is configured to send a signaling message to an IP address of the destination terminal.

7. (Original) The apparatus as set forth in Claim 1 wherein said test controller is configured to send a signaling message to a device controller within said telecommunication device, said device controller allocating the allocated voice path.

8. (Previously Presented) The apparatus as set forth in Claim 1 wherein the allocated voice path provides a connection to a media gateway for converting between circuit-switched voice and packet-switched voice.

DOCKET NO. 2003.10.010.NS0  
U.S. SERIAL NO. 10/810,302  
PATENT

9. (Currently Amended) A telecommunication system for testing a telecommunication device comprising switching fabric including a plurality of voice paths, said telecommunication system comprising:

an originating terminal ~~placing a test call~~ configured to generate a test call initiation message;

and

a test controller configured to receive the test call initiation message from the originating terminal, the test call initiation message being directed to the test controller, to prompt the telecommunication device to allocate one of the voice paths within the telecommunication device for ~~[[the]]~~ a test call based on the test call initiation message, and to establish a call connection for the test call between the originating terminal and a destination terminal via the allocated voice path and a packet-switched network to test the allocated voice path.

10. (Original) The telecommunication system as set forth in Claim 9 wherein the voice paths comprise time division multiplexed (TDM) switched circuits.

DOCKET NO. 2003.10.010.NS0  
U.S. SERIAL NO. 10/810,302  
PATENT

11. (Original) The telecommunication system as set forth in Claim 9, further comprising:

a media gateway connected to said telecommunication device and the packet-switched network to convert between circuit-switched voice transmitted by said telecommunication device and packet-switched voice transmitted over the packet-switched network, the allocated voice path being connected to said media gateway for the test call.

12. (Previously Presented) The telecommunications system as set forth in Claim 9, wherein said telecommunication device comprises:

switching fabric including a plurality of voice circuits for switching voice calls; and

a controller operable to receive a signaling message from said test controller to establish the call connection for the test call through the packet-switched network, said controller being further operable to allocate one of the voice circuits for the test call to test the allocated voice circuit.

13. (Original) The telecommunication system as set forth in Claim 9 wherein the originating terminal and the destination terminal are Session Initiation Protocol (SIP) phones.

DOCKET NO. 2003.10.010.NS0  
U.S. SERIAL NO. 10/810,302  
PATENT

14. (Currently Amended) The telecommunication system as set forth in Claim 13 ~~wherein said test controller is configured to receive a signaling message for the test call from the originating terminal, the signaling~~ the test call initiation message being addressed to an Internet Protocol (IP) address of said test controller.

15. (Currently Amended) The telecommunication system as set forth in Claim 14 wherein the signaling test call initiation message is an INVITE message.

16. (Original) The telecommunication system as set forth in Claim 14 wherein said test controller is configured to send a signaling message to an IP address of the destination terminal.

17. (Original) The telecommunication system as set forth in Claim 9 wherein said test controller is configured to send a signaling message to a device controller within said telecommunication device, said device controller allocating the allocated voice path.

18. (Original) The telecommunication system as set forth in Claim 9 wherein said telecommunication device is a switch.

19. (Original) The telecommunication system as set forth in Claim 18 wherein said switch is a mobile switching center.

LASAMS01W0320

-6-

DOCKET NO. 2003.10.010.NS0  
U.S. SERIAL NO. 10/810,302  
PATENT

20. (Currently Amended) For use in a telecommunication system comprising a telecommunication device, said telecommunication device comprising switching fabric including a plurality of voice paths, a method of testing the voice paths in said telecommunication device, the method comprising the steps of:

receiving a ~~signaling message~~ for a test call initiation message directed to a test controller from an originating terminal;

sending a signaling message to the telecommunication device to allocate one of the voice paths for ~~[[the]]~~ a test call in the telecommunication device based on the test call initiation message;

establishing a connection between the originating terminal and a destination terminal for the test call through a packet-switched network using the allocated voice path; and

testing the allocated voice path during the test call.

21. (Original). The method as set forth in Claim 20 further comprising the step of converting between circuit-switched voice transmitted by said telecommunication device and packet-switched voice transmitted over the packet-switched network.

22. (Currently Amended) The method as set forth in Claim 20 wherein said step of receiving further comprises receiving the ~~signaling~~ test call initiation message addressed to an Internet Protocol (IP) address of ~~[[a]]~~ the test controller.

DOCKET NO. 2003.10.010.NS0  
U.S. SERIAL NO. 10/810,302  
PATENT

23. (Currently Amended) The method as set forth in Claim 22 wherein the signaling test call initiation message is a Session Initiation Protocol (SIP) INVITE message.

24. (Original) The method as set forth in Claim 22 wherein said establishing further comprises sending a signaling message from the test controller to an IP address of the destination terminal.